



Warren Paint and Color Co.

700 Wedgewood Avenue (at I-65)
Nashville, Tennessee 37203
www.warrenpaint.com
Phone: 615-292-6655 / Fax: 615-292-6654
Emergency: 800-535-5053

Prepared: April 1, 2009

Product Data Sheet

1301
Satin Walco
Interior Flat Latex Wall Paint

Velvet Flat Finish
Available in Many Colors
Excellent Washability

Satin Walco is the premium flat latex wall paint of the Warren product line. It is ready to use after stirring, flows on smoothly, and dries to a velvet flat finish that is dry to touch in less than one hour. It is washable and scrubable after 30 days, and has very low odor.

- Surface Preparation:** Remove all dirt, grease, and loose, peeling paint. Sand previously painted surfaces. For best results, prime with the appropriate Warren primer. Use *Vitric Enamel Undercoater* to prime wood and surfaces previously painted with oil-based enamel. *Satin Walco Primer/Sealer* is excellent for new drywall and concrete. *Super Block Filler* is best for unpainted concrete block and rough concrete. Use a *Metalcoat* primer over steel or aluminum. Allow adequate dry time before finishing with *Satin Walco*. Self-priming is possible over drywall, plaster, and concrete.
- Mixing and Thinning:** Stir or shake well. Thin sparingly with water to spray. Do not over-thin.
- Application:** Brush, roll, spray. Thin as directed. Apply between 50 and 90°F with the relative humidity less than 80%. Cover objects in the vicinity of painting to avoid paint drips or spatters.
- Dry Time:** One hour to touch. Two hours to handle. 24 hours hard
- Recoat Time:** After four hours.
- Appearance:** Velvet-flat white finish.
- Pigmentation:** Rutile titanium dioxide, aluminum and magnesium silicate, and calcium carbonate.
- Vehicle:** Vinyl acrylic copolymer emulsion.
- % Solids by Weight:** 53.7
- % Solids by Volume:** 33.8
- Coverage:** 387 square feet per gallon at 1.4 mils DFT (100% transfer and zero profile). Realistically 75-150 square feet per gallon over extremely rough surfaces. Approximately 400 square feet per gallon is possible over previously primed or painted drywall.
- V.O.C.:** 0.25 lb/gal (31 g/l) with water; 0.69 lb/gal (83 g/l) without water.
- Cured Film Properties:** Tough, flexible film with good washability.
- Standard Packaging:** One gallon cans. Fives and drums are available by special order.